

TDS11-SA – AS IS, COMPLETE SYSTEM: \$ 650,000 USD



Technical Specification:

Load Path: 500 Ton
Mud Path: 5000 PSI
Motor Rating: 800 HP

Torque Rating:

Max Torque: 55,000 Ft.-Lbs
Drilling Torque: 37,500 Ft.-Lbs
Static Lock brake: 39,000 Ft.-Lbs.

This quotation is subject to GDS's standard terms and conditions, which are at www.globaldrillingsupport.com/termsandconditions



9841 Windmill Park Ln.
Houston, TX 77064
+1 713-623-1449
sales@globaldrillingsupport.com

Top Drive Control VFD House:

Top Drive control system with MCC to run required auxiliary motors, Set up to operate at 600 VAC 60 HZ
Insulated building with required air conditioning and lighting
Suitable plug board for quick rig up and down

Service Loop Kit Includes:

Cables to reach from the top drive to the control house
Set up for a standard 136 to 142 mast

Top Drive Control Console Includes:

All control buttons and meters to operate the top drive unit
Stainless steel enclosure

Top Drive Track:

Guide Track suitable for a Triple 136ft -142ft mast

Notes:

- GDS is a QMS registered and fully licensed API 8C facility (license no. 8C-0161) and can repair, recertify and test any top drive to specification. Quote available upon request

This quotation is subject to GDS's standard terms and conditions, which are at www.globaldrillingsupport.com/termsandconditions

www.GlobalDrillingSupport.com